

Customer No. 20350
TOWNSEND and TOWNSEND and CREW LLP
Two Embarcadero Center, 8th Floor
San Francisco, California 94111-3834
(415) 576-0200

ASSISTANT COMMISSIONER FOR PATENTS
BOX PATENT APPLICATION
Washington, D.C. 20231

11/12/99
JC662 U.S. PTO

Attorney Docket No. 939A-350-1-2

"Express Mail" Label No. EL115551016US
Date of Deposit: November 12, 1999

I hereby certify that this is being deposited with the U.S. Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above, addressed to:

Assistant Commissioner for Patents
Washington, D.C. 20231

By: *Sumit But*

Sir:

Transmitted herewith for filing is the

[X] divisional patent application of

The PTO did not receive the following
listed item(s): 3 drawings

Inventor(s)/Applicant Identifier: ROBERT J. PROEBSTING

For: HIGH SPEED VIDEO FRAME BUFFER

- [X] This application claims priority from each of the following Application Nos./filing dates:
60/023,955/Aug 09, 1996; 08/884,845/Jun 30, 1997; and 09/179,260/Oct 26, 1998,
the disclosure(s) of which is (are) incorporated by reference.
- [X] Please amend this application by adding the following before the first sentence: "This application is a [x] Division of and claims the benefit of U.S. Application No. 09/179,260, filed October 26, 1998, which is a Division of U.S. Application No. 08/884,845, filed June 30, 1997, which is a Continuation of Provisional Application No. 60/023,955, filed August 9, 1996, the disclosures of which are incorporated by reference."
- [X] Please enter the enclosed preliminary amendment.

Enclosed are:

- [X] 3 sheet(s) of [X] formal [] informal drawing(s).
- [X] Information Disclosure Statement under 37 CFR 1.97.
- [X] A copy of the declaration, specification and claims from the parent application.

	(Col. 1)	(Col. 2)	
FOR:	NO. FILED	NO. EXTRA	
BASIC FEE			
TOTAL CLAIMS	6 - 20	= *0	
INDEP. CLAIMS	2 - 3	= *0	
[] MULTIPLE DEPENDENT CLAIM PRESENTED			

SMALL ENTITY		OR	OTHER THAN SMALL ENTITY	
RATE	FEE		RATE	FEE
	\$380.00	OR		\$760.00
x \$9.00 =		OR	x \$18.00 =	\$0.00
x \$39.00 =		OR	x \$78.00 =	\$0 00
+ \$130.00 =		OR	+ \$260.00 =	
TOTAL		OR	TOTAL	\$760.00

Please charge Deposit Account No. 20-1430 as follows:

- [X] Filing fee \$ 760.00
- [X] Any additional fees associated with this paper or during the pendency of this application.
- [] A check for \$ _____ is enclosed.
- 2 extra copies of this sheet are enclosed.

Respectfully submitted,

TOWNSEND and TOWNSEND and CREW LLP

Babak S. Sani
Babak S. Sani
Reg No.: 37,495
Attorneys for Applicant


Telephone: (415) 576-0200
Facsimile: (415) 576-0300

"Express Mail" Label No EL115551016US
Date of Deposit November 12, 1999

PATENT
Attorney Docket No.: 939A-350-1-1

I hereby certify that this is being deposited with the United States Postal
Service "Express Mail Post Office to Address" service under 37 CFR 1.10
on the date indicated above and is addressed to

Assistant Commissioner for Patents
Washington, D.C. 20231

By 

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of:

PROEBSTING

Application No.: Not Assigned

Filed: Herewith

For: HIGH SPEED VIDEO FRAME
BUFFER

Examiner: To be announced

Art Unit: To be announced

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Prior to examination of the above-referenced application, please enter the
following amendments and remarks.

IN THE SPECIFICATION:

At page 6

line 2, please delete "commonly-assigned";

line 3, please replace "Application Number 08/____,____ (Atty Docket
No. 00939A-0331)" with -- Number 5,793,383 to Proebsting, entitled "Shared Bootstrap
Circuit" -- and

line 20, please replace "unasserted" with --de-asserted --.

IN THE CLAIMS:

Please cancel claims 1-19 and add new claims 20-25 as follows:

1 --20. (New) In a video data processing apparatus including a controller coupled
2 to a memory circuit that has a plurality of arrays, a method for storing video data in the
3 memory circuit comprising the steps of:

4 segmenting a plurality of pixels representing one horizontal line of an image
5 display panel into a plurality of pixel groups; and

6 storing data representing each of said plurality of pixel groups, respectively, in a
7 row of a plurality of non-adjoining arrays in the memory circuit.

1 21. (New) The method of claim 20 further comprising the steps of:

2 defining tiles of pixels by a two-dimensional grouping of the plurality of pixel
3 groups from a plurality of horizontal lines of the display panel; and

4 storing data representing each tile of pixels substantially entirely in non-
5 adjoining arrays in the memory circuit.

1 22 (New) The method of claim 21 wherein the data representing each of said
2 plurality of pixel groups is respectively stored in the same row of the plurality of non-adjoining
3 arrays.

1 23. (New) The method of claim 22 wherein the data representing each tile of
2 pixels is respectively stored in consecutive rows of the plurality of non-adjoining arrays.


1 24. (New) The method of claim 23 further comprising the steps of:
2 dividing the display panel into a first half and a second half;
3 storing pixel data from the first half of the panel in odd numbered arrays in the
4 memory circuit; and
5 storing pixel data from the second half of the panel in even numbered arrays in
6 the memory circuit.

1 25. (New) In a video data processing apparatus including a controller coupled
2 to a memory circuit that has a plurality of arrays, a method for storing video data in the
3 memory circuit comprising the steps of:
4 dividing the display panel into a first half and a second half;
5 storing pixel data from the first half of the panel in odd numbered arrays in the
6 memory circuit; and
7 storing pixel data from the second half of the panel in even numbered arrays in
8 the memory circuit.--

REMARKS

By this amendment claims corresponding to the non-elected claims in the parent application have been presented for examination.

Respectfully submitted,


Babak S. Sani
Reg. No. 37,495

TOWNSEND and TOWNSEND and CREW LLP
Two Embarcadero Center, 8th Floor
San Francisco, California 94111-3834
Tel: (415) 576-0200
Fax: (415) 576-0300
BSS:deb
SF 1042366 v1

PATENT APPLICATION

HIGH SPEED VIDEO FRAME BUFFER

Inventor:

Robert J. Proebsting, a citizen of United States, residing at 27800 Edgerton Road, Los Altos Hills, CA 94022.

Assignee:

Townsend and Townsend and Crew, LLP

TOWNSEND and TOWNSEND and CREW LLP
Two Embarcadero Center, 8th Floor
San Francisco, California 94111-3834
(415) 576-0200

HIGH SPEED VIDEO FRAME BUFFER

5

BACKGROUND OF THE INVENTION

This invention relates in general to video electronics, and in particular to a high speed video display memory using dynamic memory cells implemented on the same chip as the video display controller.

10

A typical computer system includes a video card that carries the circuitry for processing video signals and for driving the display panel. Figure 1 shows a conventional video card 100 that includes a display memory chip 102 (sometimes referred to as a frame buffer) connected to a controller chip 104 via input/output (I/O) pins 106. Display memory 102 stores data that represent the color or intensity of light for every picture cell (pixel) on the video screen, and controller 104 processes the data and drives the display. A drawback of this type of system is limited bandwidth between the memory and the controller caused by the limited number of data input/output pins 106 on the two chips.

15
20

It is desirable to substantially increase the rate of data transfer between the video memory and the video processor. Using a memory system with multiple banks improves the bandwidth somewhat. For example, dual-bank video memories have been developed whereby two word lines one from each bank can be selected at the same time. While some improvement is achieved by this design, still higher bandwidths are required.

25

Integrating both the memory circuit and the controller on the same chip is a solution that promises a significant increase in the bandwidth. With the memory on the same chip as the processor, instead of e.g., 32 bits over 32 I/O pins, 128 or 256 bits can be accessed internally at very high speeds.

30

SUMMARY OF THE INVENTION

The present invention offers an improved video memory circuit that is integrated on the same chip as the video controller. The memory circuit is arranged in a plurality of memory cell arrays that are separated by clusters of sense amplifiers. Each cluster of sense amplifiers is shared by two adjacent dynamic memory arrays resulting in a compact design that minimizes circuit area.

In a typical dynamic memory, such as a dynamic random access memory (DRAM), access to a given cell usually occurs in two steps. First a row is open then a column within that row is selected. Access to a column in a previously open row is relatively fast while access to a column in any other row is slow. Instead of activating an array only when a word line from that array is selected and then turning the array off after the data has been accessed, the present invention maintains the maximum number of arrays activated at any given time. That is, once an array is selected, it is not turned off until it receives a command from the processor selecting a new row in that array or an array adjacent to it. Because in the memory circuit of the present invention adjacent arrays share the same group of sense amplifiers, when the memory receives a new command selecting a word line from array N, any previously selected word lines from array N as well as arrays N-1 and N+1 are first turned off. The bit lines are then equilibrated and array N is then reopened to the appropriate address. The processor keeps track of which arrays are active and which rows are selected and which ones are off.

This scheme allows half of the arrays to be selected at the same time. By specifically organizing the data such that a large number of adjacent pixels that are typically manipulated together are stored within those arrays that can be active simultaneously, the memory bandwidth is maximized. For example, the display screen can be divided into a bottom half and a top half. Pixel data corresponding to the bottom half can be stored in for example all odd numbered arrays and pixel data corresponding to the top half can be stored in the even numbered arrays. Since most of the time all pixel data that are manipulated as a group would be stored in either even numbered or odd numbered arrays, all of those arrays can be accessed at one time, and as many word lines as half the number of arrays in the memory can be selected simultaneously. Thus,

access to read or write the memory is provided at a very high bandwidth. There is also less power consumed as the word lines are not turned off and on for every access.

Accordingly, in one embodiment, the present invention provides a method for operating a memory circuit having a plurality of arrays including the steps of (a) receiving a command accessing array N, (b) turning off arrays N, N+1 and N-1, (c) equilibrating bit lines in array N, and (d) turning on array N to access a selected word line.

In another embodiment, the present invention provides a method for operating a memory circuit having a plurality of arrays including the steps of (a) receiving a first command accessing a row in a first array, (b) turning on the first array to allow access to memory cells in that row, and (c) keeping the first array open until it receives a second command accessing a new row in the first array. The method further includes a step of turning off the first array upon receipt of the second command, and turning off a second array adjacent to the first array.

A better understanding of the nature and advantages of the high speed video memory circuit of the present invention may be had with reference to the detailed description and the drawings below.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a simplified block diagram of a video card including a memory chip and a controller chip;

Figure 2 is a conceptual block diagram of the multiple-array memory circuit according to the present invention;

Figure 3 is an exemplary circuit schematic of an array enable logic; and

Figure 4 illustrates exemplary divisions of pixels on a video display screen for data storage in the memory arrays to maximize memory bandwidth according to the present invention.

DESCRIPTION OF SPECIFIC EMBODIMENTS

Referring to Figure 2, there is shown a block diagram of a memory circuit 200 having multiple arrays A_0 to A_n according to one embodiment of the present invention. An array A_i may include for example 256 rows of e.g., 1024 memory cells. With these exemplary numbers, each array stores 256 Kbits of data. To reduce the size of the memory circuit, according to a preferred embodiment of the present invention, adjacent arrays share clusters of bit line sense amplifiers S/A_1 to S/A_n . With the example used herein, each cluster of sense amplifiers includes 512 individual sense amplifier circuits that serve two arrays one on either side.

Data is written into and read from the memory cells in each array via multiple global input/output GIO lines that selectively connect to the bit lines in arrays A_0 to A_n via column select circuits (not shown). The width of this data bus corresponds to the memory I/O bus that connects the memory to the controller on the same die. There may be, for example, 128 parallel differential pairs of GIO lines $GIO<0>$ to $GIO<127>$ that traverse the entire array. In such an exemplary case, there would be a corresponding number (128) of write driver and I/O sense amplifier circuits (not shown) that connect the memory I/O bus to the 128 pairs of GIO lines. Each array A_i further connects to an output terminal of an array enable circuit AE_i . An array enable circuit AE_i turns its associated array A_i on or off in response to control signals it receives from the video controller (not shown).

For illustrative purposes, Figure 2 depicts arrays A_0 to A_n stacked in a single column of arrays. The arrays may in fact be grouped into two or more stacks. For example, the memory circuit may include 64 arrays of 1024x256 bits grouped as four stacks of 16 arrays each. With one qualification, each array A_i operates almost as an independent memory unit via the common memory I/O bus. Because neighboring arrays in the memory circuit of the present invention share bit line sense amplifiers, two adjacent arrays are not permitted to simultaneously have open rows. Thus, the memory circuit allows up to half of the arrays to have open rows at any given time. Using the above exemplary numbers, given 64 1024-bit wide arrays, there will be 32 Kbits available for column access. According to this invention, once an array is activated on a row, it remains active on that row until it is activated on a different row or until one of

its neighboring arrays is activated. Thus, repeated accesses can be made to the same row of up to 32 already activated arrays without having to go through a precharge cycle. The row addresses of the open rows need not be the same. This technique allows for maximizing the memory bandwidth by organizing and storing pixel data in the various arrays to take full advantage of the multiple simultaneously active arrays.

The following exemplary numbers are used herein to describe the operation of the memory circuit in greater detail. It is assumed that it will take 20ns to precharge (turn off previously on row and equilibrate bit lines), 30ns to select and turn on a new row, making a column access possible, and 20ns from the time a column is selected until the data is made available, for a maximum access time of 70ns. Accordingly, referring to Figure 2, when a new row in an array A_i is selected, regardless of whether that array or its two neighboring arrays A_{i+1} and A_{i-1} were on or off, the total access time would be 70ns. This is slightly longer than a total access time of 50ns for the prior art memories where the precharge time would not be included in the access time. In the prior art circuit, however, a selected row is usually shut down after the completion of the cycle. Thus, in this circuit if in a subsequent cycle access is made to a different column in the same row, the total access time remains 50ns.

According to the present invention, however, once a specific row in an array is activated, that row remains open. Using the exemplary numbers, with the row already open, it takes only 20ns to access a new column in that row. The controller may open a row in a second non-neighboring array while keeping the row in the first array open. A new array can be activated every 10ns, provided it does not conflict with the activation in progress with a neighboring array. Continuing in that fashion, up to 32 of the 64 arrays may have simultaneously active rows. Thus, data can be accessed and transferred at a very fast rate as long as it resides in the various simultaneously active rows.

Referring to Figure 3, there is shown an exemplary circuit diagram for the word line enable logic. The output of the exemplary circuit shown in Figure 3 generates the word line enable signal WL_EN that activates a pump circuit that boosts the voltage level on the selected word line. To further reduce the circuit area, two adjacent memory

arrays may share the word line boost circuit, since both cannot be active simultaneously. The shared word line boost circuit is the subject of a commonly-assigned, related pending United States Patent Application Number 08/____,____ (Atty Docket No. 00939A-0331), which is hereby incorporated in its entirety for all purposes.

5

Assuming a given word line enable signal WL_EN drives a word line boost circuit that is shared by arrays A_i and A_{i+1} , the word line enable logic must implement the following functions:

- 10 (1) At time t_0 , WL_EN is turned OFF when either one of arrays A_i or A_{i+1} is activated.
- (2) At time t_{20} , WL_EN is turned ON when either one of arrays A_i or A_{i+1} is activated.
- (3) At time t_0 WL_EN is turned OFF when array A_{i-1} is activated when array A_i was active.
- 15 (4) At time t_0 WL_EN is turned OFF when array A_{i+2} is activated when array A_{i+1} was active.

As described above, when a new row in an array is selected, according to the present invention, any open rows in that array are first turned off at time t_0 to allow for precharging. Condition (1) is implemented by transistors 308 or 314. When array A_i or A_{i+1} is activated, signals t_0-A_i or t_0-A_{i+1} are respectively asserted at time t_0 and unasserted before time t_{20} . When signal t_0-A_i goes high, transistor 308 is turned on pulling node 316 down to ground, overpowering latch 317. Signal WL_EN is turned low turning off the previously selected word line. Similarly, when signal t_0-A_{i+1} goes high, transistor 314 is turned on, pulling node 316 down to ground, and causing WL_EN to go low.

25

Condition (2) refers to the turning on of the new word line in the array at time t_{20} upon completion of the precharge cycle and to access the selected row. This is accomplished by NOR gate 300 and PMOS transistor 302. When a logic high is applied to either one of the inputs $t_{20}-A_i$ or $t_{20}-A_{i+1}$, transistor 302 is turned on pulling node 316 up to V_{cc} , again powering latch 317. This causes WL_EN to go high activating the new selected word line.

30

The other two conditions refer to when a new array (A_{i+1} or A_{i+2}) is selected at time t_0 adjacent to an already selected array (A_i or A_{i+1}). In either case, a pair of transistors 304/306 or 310/312 are turned on pulling node 316 down to ground, and causing WL_EN to turn off.

5

To maximize the bandwidth, the preferred embodiment of the present invention maximizes the likelihood of consecutive accesses to already open rows. This can be accomplished by cleverly dividing where in the array pixel data is stored. Referring to Figure 4, there is shown a simplified video screen 400 of, for example, 1024x512 size. The video controller processes pixel data in two modes. When displaying the pixels, the screen is scanned horizontally starting from the top line L(0) to the bottom line L(511) of the screen. At other times, the controller may process a, for example, 32x32 tile of pixels.

10

15

One example of distributing pixel data to take advantage of the open arrays in the memory circuit of the present invention divides the screen into a top half and a bottom half. Pixel data corresponding to the top half of the screen are stored in even numbered memory arrays, and pixel data corresponding to the bottom half of the screen are stored in the odd numbered memory arrays. If each pixel is represented by 32 bits of data, then a 1024-bit row in an array can store data corresponding to 32 pixels. Accordingly, the first group 32 pixels in line L(0) are stored in row 0 of array 0, the second group of 32 pixels in line L(0) are stored in row 0 of array 2, the third group of 32 pixels in line L(0) are stored in row 0 of array 4, etc. With this type of distribution, all the data required to display line L(0) on the screen 400 can be simultaneously available in already open rows in even numbered arrays.

20

25

A similar distribution technique is preferably employed for storing each 32x32 tile of pixels. That is, the first row of the first tile is stored in Row 0 of Array 0 as discussed. The second row of the first tile is stored in Row 1 of Array 2, etc. This distribution is partially shown in Figure 4. With each row of a given tile in different arrays which can be simultaneously open, all the data for a given tile can be in open rows. When data is manipulated in tiles, performance significantly improves by fast access to the full contents of any tile. Thus, data is transferred at a significantly faster

30

rate as long as consecutive accesses are made to the same set of open rows. Power dissipation is also reduced by reducing the number of times arrays are required to be turned off and on. It is to be understood that other common screen sizes such as 1024 x 678 or 1280 x 1024 as well as other numbers of bits per pixel such as 8, 16, or 24 can also be arranged with an appropriate memory size to open either a full row of screen data or a full tile.

In conclusion, the present invention provides a memory circuit that is particularly suited for video applications. The memory circuit of the present invention achieves much higher bandwidth and reduced power consumption by maintaining the maximum number of memory arrays open simultaneously. Circuit area is also saved by sharing bit line sense amplifiers between adjacent arrays. A specific video memory circuit which incorporates an exemplary embodiment of the present invention as well as other related circuit techniques is described in greater detail in the article entitled "An Embedded Frame Buffer for Graphics Applications," attached herein as Appendix A.

While the above is a complete description of specific embodiments of the present invention, various modifications, variations and alternatives may be employed. The scope of this invention, therefore, should not be limited to the embodiments described, and should instead be defined by the following claims.

WHAT IS CLAIMED IS:

1 1. A method for operating a memory circuit having a plurality of
 2 arrays comprising the steps of:
 3 (a) receiving a first command accessing a row in a first array;
 4 (b) opening said first array to allow access to memory cells coupled to said
 5 row; and
 6 (c) keeping said first array open until said array receives a second
 7 command accessing a different row in said first array.

1 2. The method of claim 1 further comprising a step of turning off
 2 said first array and a second array adjacent to said first array upon receipt of said second
 3 command.

1 3. The method of claim 2 wherein said step of turning off said first
 2 array occurs also in response to receipt of a third command accessing a row in said
 3 second array adjacent to said first array.

1 4. A method for operating a memory circuit having a plurality of
 2 arrays comprising the steps of:
 3 (a) receiving a command accessing array N;
 4 (b) turning off arrays N, N+1 and N-1;
 5 (c) equilibrating bit lines in array N; and
 6 (d) turning on array N to access a selected word line.

1 5. A memory circuit comprising:
 2 a plurality of arrays of memory cells, each array having n columns and m
 3 rows, with a memory cell coupled at each cross section of a row and a column; and
 4 a plurality of clusters of sense amplifiers, each of said plurality of arrays
 5 being sandwiched by a pair of said plurality of clusters of sense amplifiers, each cluster of
 6 sense amplifiers having n/2 sense amplifier circuits coupling to n/2 columns in an
 7 associated array,

8 wherein, up to half of said plurality of arrays may be active simultaneously.

9
1 6. The memory circuit of claim 5 further comprising a plurality of
2 array enable logic blocks coupled to said plurality of arrays.

1 7. The memory circuit of claim 6 wherein one of said plurality of
2 array enable logic blocks activates an associated array when a row in said array is selected
3 and keeps said array active until a different row in said array, or a row in an adjacent
4 array is selected.

1 8. A video chip comprising:
2 a memory circuit;
3 controller logic; and
4 a wide bus coupling said memory circuit to said controller logic,
5 wherein, said memory circuit comprises:
6 a plurality of arrays of memory cells, each array having n columns and m rows,
7 with a memory cell coupled at each cross section of a row and a column; and
8 a plurality of clusters of sense amplifiers, each of said plurality of
9 arrays being sandwiched by a pair of said plurality of clusters of sense amplifiers,
10 each cluster of sense amplifiers having $n/2$ sense amplifier circuits selectively
11 coupling to $n/2$ columns in an associated array,
12 wherein, up to half of said plurality of arrays may be active simultaneously
13 allowing said controller to access more data via said wide bus.

1 9. The video chip of claim 8 wherein video data representing video
2 display pixel information are stored in said memory circuit whereby data representing one
3 tile is stored in one row per array in non-adjoining arrays.

1 10. The video chip of claim 8 wherein said plurality of arrays are
2 organized in two or more groups of arrays, and each array comprises at least 1024
3 columns and at least 256 rows.

1 11. The video chip of claim 8 wherein said wide bus is at least 128 bits
2 wide.

1 12. The video chip of claim 9 wherein data comprising any given tile of
2 pixels is stored substantially entirely in either even numbered arrays or substantially
3 entirely in odd numbered arrays.

1 13. The video chip of claim 9 wherein said data comprising any given
2 tile of pixels is stored in rows that can be simultaneously activated.

1 14. The video chip of claim 9 wherein data comprising any given screen
2 display line is stored substantially entirely in one row per array in non-adjointing arrays.

1 15. The video chip of claim 14 wherein said data comprising any given
2 screen display line is stored substantially entirely in either even numbered arrays or
3 substantially entirely in odd numbered arrays.

1 16. The video chip of claim 15 wherein said data comprising any given
2 screen display line is stored in rows that can be simultaneously activated.

1 17. The video chip of claim 12 wherein data comprising any given
2 screen display line is stored substantially entirely in either even numbered arrays or
3 substantially entirely in odd numbered arrays.

1 18. The video chip of claim 17 wherein said data comprising any given
2 tile of pixels is stored in rows that can be simultaneously activated.

1 19. The video chip of claim 18 wherein said data comprising any given
2 screen display line is stored in rows that can be simultaneously activated.

HIGH SPEED VIDEO FRAME BUFFER

ABSTRACT OF THE DISCLOSURE

5 A memory circuit achieves much higher bandwidth and reduced power
consumption by maintaining the maximum number of memory arrays open
simultaneously. Circuit area is also saved by sharing bit line sense amplifiers between
adjacent arrays. When selected, an array remains open until a different row in the same
array or an array adjacent to it is selected. Thus, as long as access is made to an open
row of every other array, access time and power are reduced by eliminating the need to
10 turn arrays on and off.

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I declare that:

My residence, post office address and citizenship are as stated below next to my name; I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: **HIGH SPEED VIDEO FRAME BUFFER** the specification of which ___ is attached hereto, or x was filed on June 30, 1997 as Application No. ___ and was amended on ___ (if applicable).

I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, Section 1.56. I claim foreign priority benefits under Title 35, United States Code, Section 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

Country	Application No.	Date of Filing	Priority Claimed Under 35 USC 119
			Yes _ No _
			Yes _ No _

I hereby claim the benefit under Title 35, United States Code §119(e) of any United States provisional application(s) listed below:

Application No.	Filing Date
60/023,955	8/9/96

I claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, Section 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Application No.	Date of Filing	Status
		_ Patented _ Pending _ Abandoned
		_ Patented _ Pending _ Abandoned


POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

Robert C. Colwell, Reg. No. 27,431
Babak S. Sani, Reg. No. 37,495


Send Correspondence to: Babak S. Sani TOWNSEND and TOWNSEND and CREW LLP Two Embarcadero Center, 8th Floor San Francisco, CA 94111-3834	Direct Telephone Calls to: (Name, Reg. No., Telephone No.) Name: Babak S. Sani Reg. No.: 37,495 Telephone: 415/576-0200
---	--

Full Name of Inventor 1	Last Name PROEBSTING	First Name ROBERT	Middle Name or Initial J.	
Residence & Citizenship	City Los Altos Hill	State/Foreign Country CA	Country of Citizenship U.S.A.	
Post Office Address	Post Office Address 27800 Edgerton Rd.	City Los Altos Hills	State/Country CA	Zip Code 94022
Full Name of Inventor 2	Last Name	First Name	Middle Name or Initial	
Residence & Citizenship	City	State/Foreign Country	Country of Citizenship	
Post Office Address	Post Office Address	City	State/Country	Zip Code
Full Name of Inventor 3	Last Name	First Name	Middle Name or Initial	
Residence & Citizenship	City	State/Foreign Country	Country of Citizenship	
Post Office Address	Post Office Address	City	State/Country	Zip Code

I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Signature of Inventor 1  ROBERT J. PROEBSTING	Signature of Inventor 2	Signature of Inventor 3
Date 7/23/97	Date	Date

United States Patent & Trademark Office
Office of Initial Patent Examination -- Scanning Division



Application deficiencies were found during scanning:

☐ Page(s) 3 of Drawings were missing were not present
for scanning. (Document title)

☐ Page(s) _____ of _____ were not present
for scanning. (Document title)

☐ Scanned copy is best available.